



**09, 16, 19, 20, 21,
24, 28, 28C, 36, 36C
39, 50, 56LW &
58LW Series
Installation**

Auto racing remains a very dangerous sport regardless of any protective devices you may use. Please read the instructions very carefully and if you have any questions please contact Kirkey Racing Fabrication Inc. 1-800-363-4885.

**FAILURE TO COMPLY WITH THESE INSTRUCTIONS MAY CAUSE
SERIOUS INJURY OR DEATH.**

MOUNTING INSTRUCTIONS

This seat is to be mounted using the following instructions. For the bottom of the seat, we recommend that you use no less than four (4) 5/16" (8mm) bolts directly through the bottom of seat to the frame or roll cage. (spread the bolts out as far as possible to distribute the load). For the back of the seat, we recommend no less than two (2) 5/16" (8mm) bolts through the back of the seat (below the shoulder belt openings) to the roll cage. NEVER mount to sheet metal.

If you are not qualified to perform such fabrication have the installation done by an expert familiar with the requirements of such installation.

We DO NOT recommend the use of stock sliders and adjusters.

Be sure to check with your sanctioning body and/or track for their rules and regulations on seat mounting.

For more information please contact us
www.kirkeyracing.com kirkey@kirkeyracing.com
1-800-363-4885 (voice) 1-800-829-7072 (fax)

Not intended for highway or airplane use.